



## PERFORMANCE HEADER TRANSPORT

Loading and transporting your MacDon headers just got a whole lot easier with MacDon TR Series Trailers. Specifically built for your MacDon header, the swan neck chassis design provides on-road precision for up to 40 km/h (24 mph) road speeds.\*

*\*Always follow local traffic laws and regulations.  
Only use towing vehicles rated to tow MacDon Trailers.*

*\*\*Some products and/or options may not be available in all markets.  
See your MacDon Dealer for availability.*

## FEATURES

### **A** PRECISION TRANSPORT

The swan neck chassis design provides on-road precision, allowing the trailer to follow the towing vehicle's tracks closely. This design lets you handle tight roadways and crossings with confidence.

### **B** ROAD READY HOMOLOGATION

MacDon Trailers can be used with windrowers, combines or tractors. MacDon TR Series Trailers have EU homologation for 40 km/h (24 mph) and comply with European road standards.\*

*\*Always follow local traffic laws and regulations.  
Only use towing vehicles rated to tow MacDon Trailers.*

### **C** EASY ON. EASY OFF.

Loading and unloading your MacDon headers just got a whole lot easier with MacDon-specific header supports/hooks.

### **D** HIT THE BRAKES

The inertia-activated brake activates the front and rear drum brakes via cable tension. Inertia braking allows for smooth handling of the trailer by the towing vehicle.

Trailers are equipped with a hand-activated park brake, wheel chocks, and on-frame wheel chock storage.



## PERFORMANCE OPTIONS

### A SPARE TIRE OPTION

Conveniently stored on-frame to quickly get you back on the road and in the field harvesting.



### B ON-FRAME STORAGE

An optional storage box is cleverly attached on-frame and allows storage of tools and performance options like crop dividers and crop lifters. A vertical knife storage rack is also available.



### C VERTICAL KNIFE STORAGE RACK

Vertical Knife Storage Rack option available.\*

\*Not compatible with 2-Series VertiBlade™.



## SPECIFICATIONS

### TR Series Trailer Specifications

Model	TR25
Weight	1710 kg (3770 lb)
Dimensions	Length: 12 m (39'4"); Width: 2.16 m (7'1")
Wheels/Brakes	P264-75 R15 radial tires; fender kit (option); inertia braking system; drum brakes; with reversing mechanism
Parking	Manual park brake; wheel chocks and wheel chock storage
Header Hookup	MacDon specific supports; adjustable alignment gauge; adjustable support arm with turnbuckles; support arms adjustable laterally; rear tie-down locations; lift-assisted tow bar
Legal	Homologated for European Union; 40 km/h (24 mph) road speed*
Storage	On-board storage box (option); On-board vertical knife storage rack (option)

\*Always Follow Local Traffic Laws And Regulations. Only Use Towing Vehicles Rated To Tow MacDon Trailers.

\*\*All Listed Weights Are Approximations And Will Vary Depending On Options Installed.

### TR Series Trailer/Header Compatibility Chart

Header Size	TR25 Compatible Header Models
4.6 m (15')*	D65, D1, D1X, D2, PW8
6.1 m (20')*	D65, D1, D1X, D2
7.6 m (25')*	D65, D1, D1X, FD125, D2, FD225
C Series	Max header size = 12 row x 50.8 cm (20") row spacing

\*D1 Headers equipped with a TM100 Tractor Mount can be used with MacDon Trailers.